

PRODUCT INFORMATION SHEET

MARCH 2015

INEX>FLOOR is a revolutionary, low carbon, high strength yet lighter weight for ease of handling cement based flooring sheet suitable for both interior and exterior flooring applications.

INEX>FLOOR has a tongue and groove joint down each long side for a flush tight fit.

Suitable as a substrate for most finishes such as tiles, vinyl, carpet or timber.
For approved waterproofing and coating systems, refer to the COATINGS menu at www.ubiq.com.au.

INEX>FLOOR (Polish grade) available on request.



PRODUCT	LENGTH (mm)	WIDTH (mm)	THICKNESS (mm)	Kg/m ²	Kg/Sheet
INEX>FLOOR 16	2700	600	16	20.7	33.5
INEX>FLOOR 16	2400*	600	16	20.7	29.8
INEX>FLOOR 16	1800	600	16	20.7	22.4
INEX>FLOOR 19	2700	600	19	24.6	39.9
INEX>FLOOR 19	2400*	600	19	24.6	35.4
INEX>FLOOR 19	1800	600	19	24.6	26.6

*Subject to availability or special order only.

WEIGHT

At approx. 40kg (19mm) or 34kg (16mm) per sheet the **INEX>FLOOR** sheets are lightweight and easy to handle on site.

HIGH PERFORMANCE

INEX>FLOOR can be cut and worked just like comparable fibre cement sheets, but offers improved bending strength characteristics and finish quality. **INEX>FLOOR** can span over joists up to 600mm centres.

NON-COMBUSTIBILITY

INEX>FLOOR is non-combustible and can be used in conjunction with floor systems to achieve up to BAL-FZ bush fire compliance, subject to designer's detailing.

ACOUSTIC

INEX>FLOOR's acoustic qualities offer enhanced impact sound damping when used by itself or used as a substrate for surfaces such as timber or tile.

MATERIAL

INEX>FLOOR is an advanced high strength, low carbon fibre reinforced Engineered Cementitious Composite (ECC) product, containing 60% of post industrial recycled materials. It does not contain asbestos. It is toxin free and is 100% recyclable.

VALUE

INEX>FLOOR is priced for value for the construction industry and competes strongly against all comparable products. Pricing is available on application to UBIQ or its distributors.

Selecting the right flooring product just got a whole lot simpler!

INEX>FLOOR replaces the many flooring products that are available.

INEX>FLOOR can be used for internal or external surfaces.



High Strength but Light

INEX>FLOOR is a high strength yet lightweight product weighing as little as 34kg per sheet. **INEX>FLOOR** 16mm can span over joists up to 600mm centres*.

* Refer to **INEX>FLOOR** TECHNICAL INSTALLATION SHEET for further information.

Durable

INEX>FLOOR is long-term durable and is warranted for 20 years. In the "Soak Dry" test item 6.6 of AS/NZS 2908.2:2000, **INEX>FLOOR** performs to a mean MPa of >20; test undertaken in accordance with clause 8.2.5 of AS/NZS 2908.2:2000. This represents a test pass at over 80% of the dry strength retained after 25 soak-dry cycles.

INEX>FLOOR remains stable and true as a substrate material.

Low Carbon

INEX>FLOOR is a low carbon product containing about 40% of the embodied energy of equivalent portland cement derived products.

Asbestos and Toxin Free

INEX>FLOOR does not contain any toxins and is asbestos free.

Termite Resistant

INEX>FLOOR is resistant to attack from termites.

Superior Finish

INEX>FLOOR provides a polished concrete like surface suitable as a quality finish in itself. Polish Grade available on request.

NOTE: Due to the cementitious nature of **INEX>BOARDS** some superficial pin-holing may occur.

The **smooth side** of **INEX>FLOOR** is characterised as a **Class 2** concrete finish.

Refer to **INEX>FLOOR** Technical Information Sheet for detailed information.