



MASONS
Designed Smart, Built Tough.

Hydro™



OS'Brace Panel "Seam Tape" Application Guide

Product Description

Hydro Flashing Tape is a self adhesive flashing tape that has been tested and deemed compatible to work as a joint protection between the **OS'Brace Panel**. Allowing the **OS'Brace Panel** to operate within its design Specification.

- For a risk score between 0-20 in accordance with NZBC Acceptable Solution E2/AS1
- Passed NZS3604 Building Wind Zones up to and including **'Very High'** .

Advantages

- Simple installation
- 1.2mm thick adhesive layer
- Reliable and dependable weather tightness
- Low temperature adhesion.
Can be applied as low as 5°C



This product can be obtained from the following Builders Merchants:

Mitre10, Bunnings, ITM, Carters, Placemakers.

If you have any issues in sourcing this product please contact Masons on 0800 522 533

Masons Hydro flashing tape	Roll Sizes	Masons Code
Hydro flashing tape 50mm	H 50mm x L 25m	HYDRO50x25
Hydro flashing tape 75mm	H 75mm x L 25m	HYDRO75x25



Hydro Flashing Tape is a self adhesive flashing tape that has been tested and deemed compatible to work as a joint protection between the **OS'Brace Panel**.

Order your FREE sample today! Call 0800 522 533

or visit: www.mpb.co.nz



Hydro™




Installation:

Masons Hydro Flashing Tape must be installed in accordance with these instructions.

1. **OS'Brace Panel** requires to be secured and fixed into position.
2. To ensure maximum adhesion of the tape, the substrate surface needs to be clean, dry and free from any dust or other contaminants.

Flush joint




3. Position the 50mm *Hydro* tape so that the seam between the **OS'Brace Panel** is at the center of the tape line. The *Hydro Tape* needs to completely cover the joint.
4. After application cut tape to the required length
5. To ensure that the *Hydro Tape* is properly bedded against the panels and at the edges, press the tape into position with a hard roller tool.

External Corner



3. Cut the 75mm *Hydro Tape* to length (add 50mm either side for movement).
4. Position half of the *Hydro Tape* on one wall and 'roll' it around the corner and press it into position on the adjacent wall.
5. After application cut tape to the required length
6. Finish by pressing *Hydro Tape* into position with a hard roller tool.

Internal Corner



3. Cut the 75mm *Hydro Tape* to length (add 50mm for movement).
4. Pre-fold the *Hydro Tape* in half (length ways)
5. Peel back half of the protection strip to the crease line.
6. Position the *Hydro Tape* on one wall, press it securely and tight in towards the corner. Treat with a hard roller.
7. Peel the protection strip now completely off and press firmly outwards from the corner.
7. Finish by pressing *Hydro Tape* into position with a hard roller tool.

Hydro Flashing Tape must not be stretched when joining 2 sections of tape, overlap by 100mm or more.